



[Home](#) > [Product Types](#) > [Boom Lift](#) > [Self Drive Boom Lift](#)

Self Drive Boom Lift

SD170 4x4 | 17.1m



Working Height | 17.1m (56ft)

Working Outreach | 8.7m (28ft 6in)

Safe Working Load | 200kg (440lbs)

Minimum Weight | 2750kg (6060lbs)

[VIEW PRODUCT](#)

SD210 4x4x4 | 21.3m



Working Height | 21.3m (70ft)

Working Outreach | 12.8m (42ft)

Safe Working Load | 225kg (500lbs)


Minimum Weight | 3950kg (8700lbs)

[VIEW PRODUCT](#)

Self Drive Boom Lifts Range Explained

Niftylift **self-drive boom lifts** have working heights ranging from 12m (40ft) to over 21m (69ft). Combining the capabilities of trailer mounts and self-propelled boom lifts, Nifty self-drive boom lifts are compact, lightweight and manoeuvrable. Driven from the platform while stowed, 4WD chassis options maximise traction and hydraulic outriggers allow fast setup even on rough terrain.

Easy to use proportional controls make Niftylift self-drive boom lifts simple to operate and features such as telescopic booms, fly-booms and platform rotation maximise their

tiveness on any task.

Self Drive Boom Lifts Power Options

Power options available on Nifty self-drive boom lifts include Battery, Petrol, Diesel and 'Bi-Energy' (e.g. Battery & Diesel), combining the benefits of two power sources on the same machine.*

More Self Drive Boom Lifts Information

For more information regarding our **self-drive boom lifts** or any other Nifty boom lifts, please contact Niftylift today.

* Not available on all models, check specification sheets for details of exact features.

NOT SURE WHAT YOU'RE LOOKING FOR? [SPEAK TO A MEMBER OF OUR TEAM TODAY!](#)

